Acoustic Chip Technology
Shengxin

DATASHEET

of SAW Devices

SAW Filter

Part Number: SXF0070RHNSD01

Center Frequency: 70MHz

- Package Dimensions
- Testing Environment
- Electrical Characteristics
- Frequency Characteristics
- Remark

Revision Record

Revision Number	Date	Description
SXF0070RHNSD01_V1.0	2024-05-30	Preliminary Version

All rights reserved, Copyright © Suzhou Shengxin Electronics Co., Ltd

1.Package Dimension (Unit: mm)



Attention: The mark SXFH070 is for reference.

2.MeasurementCircuit



L1=390nH, L2=390nH
Source / Load Impedance = 50Ω
Ambient Temperature = 25°C

All rights reserved, Copyright © Suzhou Shengxin Electronics Co., Ltd

3.Maximum Ratings

Rating		Value	Unit
RF Input Power	P	10	dBm
DC Voltage	V_{DC}	3	V
Operating Temperature Range	T_A	-20 ~ +70	°C
Storage Temperature Range	T_{stg}	-40~ +85	°C
ESD Voltage(MM)	V_{MM}	50	V
ESD Voltage(HBM)	V_{HBM}	175	V

4.Electrical Specification

Item	Frequency Range [MHz]	Characteristics			
		min.	typ.	max.	Unit
Center Frequency	-	69.92	70.00	70.08	MHz
Insertion Loss	-	-	19.20	20.50	dB
1dB Bandwidth	-	5.00	5.12	-	MHz
3dB Bandwidth	-	-	5.28	-	MHz
50dB Bandwidth	-	-	6.03	6.20	MHz
Amplitude Ripple	-	-	0.60	1.00	dB
Group Delay Variation	-	-	150	200	nsec
Absolute Delay Time	-	-	4.05		μsec
Absolute Attenuation	-	50	55	-	dB
Temperature Coefficient of Frequency	-94				ppm/°C
Terminating Impedance	50				Ω

1. at 25±2deg.C

All rights reserved, Copyright © Suzhou Shengxin Electronics Co., Ltd

5.Frequency Characteristics

1dB Bandwidth



3dB Bandwidth



50dB Bandwidth



DELAY



S11 Smith Chart



S22 Smith Chart



All rights reserved, Copyright © Suzhou Shengxin Electronics Co., Ltd

6.Reliability Characteristics

No.	Item	Condition to be satisfied
1	High Temp. Storage	①Test temperature: +85℃±3℃ ②Duration time：500 hours ③Restore time: 2 hours at the room temperature(25℃)
2	Low Temp. Storage	①Test temperature: -40℃±3℃ ②Duration Time: 500 hours ③Restore time: 2 hours at the room temperature(25℃)
3	High Temp. High Humidity Storage	①Test temperature: +85℃±3℃ ②Test Humidity：85%±3% ③Duration Hours：240 hours ④Restore time: 2 hours at the room temperature(25℃)
4	Temperature Cycling	①Test Temperature: -40^{0}_{-10}℃~$+85^{+10}_{0}$℃ ②Time for each step: ≥30min ③Conversion time: ≤1min ④Cycle times: 100 times ⑤Restore time: 24 hours at the room temperature(25℃)
5	Soldering heat resistance	①Reflow with 260+0/-5℃, 10±1s (Solder Pot) ②Restore time: 2 hours at the room temperature(25℃)
6	Solderability test	Soldering method and temperature: lead-free reflow soldering, 245±5 ℃ for 5±0.5s

7.Remarks

1. Please be certain not to apply voltage above the rated voltage of SAW components.
2. Please be sure that the components are operated within the specified operating temperature range.
3. Abrupt temperature change shall be avoided because deterioration of the component characteristics can occur under that situation.
4. Please be careful of soldering temperature when soldering.
5. Please do not place soldering iron on the body of components.
6. Please be careful not to subject the terminals or leads of components to excessive force.

All rights reserved, Copyright © Suzhou Shengxin Electronics Co., Ltd